



OUTDOOR OD-75

75-inch 1500 nits double-sided high brightness indoor LCD digital signage



ALL ALUMINUM



**SUNLIGHT
READABLE IMAGE**



**INTELLIGENT THERMAL
MANAGEMENT**



**WEATHER
PROOF**



**VANDAL
RESISTANT**

FOR MORE INFORMATION

For more information about CNLC, visit our website at www.cnlcdisplay.com. Copyright © cnlcdisplay. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.



SPECIFICATIONS

DIMENSIONS

MODEL

DISPLAY

TOUCH (Optional)

POWER

MECHANICAL SPECS

FEATURE

INPUT

OUTPUT

EXTERNAL CONTROL

ENVIRONMENT

INTERNAL PLAYER

CERTIFICATION

LCD Panel Size	75 inches LCD (x2)
Native Resolution	1920 x 1080
Brightness (w/o glass)	1500 nits
Color Depth	10 bits
Contrast Ratio	4000 : 1
Response Time (Typ.)	8 ms
Viewing Angle	178° / 178°
Light Lifetime (Typ.)	100,000 hrs
Blackening Defect Free	Up to 110°C (230°F)
Polarized Sunglasses Support	Yes

Detection method	Projected Capacitive Touch Technology
Input method	Finger and gloved finger
Noise Shielding	Yes
Number of simultaneous touches	Max. 40 points

Power Supply	Internal
Rated Voltage	100-120V ~ 50/60Hz 200-240V ~ 50/60Hz
Power Consumption (Typ./ Max)	1400 W / 2200 W [TBD]

Bezel Width (T/B/L/R)	255/ 91 / 91 mm
Cabinet Color	Black
Kiosk Dimension (LxHxD)	1120x2278x175 mm
Monitor Weight	220 kg
Orientation	Portrait
Glass	Double Laminated Tempered
Air Vent	Top & Bottom
Base	539.0 mm H

Language	English
Image Retention Protection	Yes
Ambient Light Sensor	Yes
Power On/Off Scheduling	Yes

HDMI 2.1 (HDCP 2.3)	x6 (1080p recommended)
DisplayPort 1.2	x2
USB 3.0	x2
Micro SD Slot	x2

Audio	x2
-------	----

RJ-45	x4 (LAN)
-------	----------

Operating Temperature	-30° C ~ 50° C
Storage Temperature	-20° C ~ 60° C
Humidity	10% ~ 100% RH Non-condensing
Water and Dust Resistant Design	IP65

Operating System	Android 8.0.0
Processor	Dual-core A73 and dual-core A53
Clock Speed	1.5GHz
Main Memory Interface	DDR4, 2G
Graphics	Quad-core MaliG51
Storage	Internal: 16GB eMMC Flash External: Support Micro SD ,Up to 32GB(exFAT) /128GB(FAT32)
Multimedia	4K 10bits VP9/H265/H264 video decoders, up to 60fps 1080P other video decoders (VC-1, MPEG-1/2/4, VP8)

CE / FCC / RoHS

Unit:mm[inch]

